

## BCS-P-EIP58VSR4-Ai2-G



Index: 11326  
GTIN13/EAN13: 5904890708631

URL: <https://bcs.pl/gb/8mpx/3398-bcs-p-eip58vsr4-ai2-g-5904890708631.html>

**BCS**  
POINT



## Product Details

<b>Product</b>	BCS-P-EIP58VSR4-Ai2-G
<b>Brand</b>	BCS POINT
<b>Camera type</b>	Dome
<b>Resolution</b>	8 Mpx
<b>Sensor</b>	1/2.8" CMOS
<b>Scanning system</b>	Progressive Scan
<b>Pixels</b>	3840(H)×2160(V)
<b>Lens</b>	motozoom
<b>Focal length</b>	2.8~12 mm
<b>Aperture</b>	F1.6
<b>Focus</b>	Auto / manual
<b>Iris</b>	Auto
<b>Optical zoom</b>	4×
<b>Digital zoom</b>	16×
<b>Angle of view</b>	H: 107.4°~ 29.2° V: 54.2°~ 16.3°
<b>DORI</b>	Detect 87~372m / Observe 35~149m / Recognize 17~74m / Identify 9~37m
<b>Min illumination</b>	0.003Lux(F1.6,AGC) 0Lux(B/W,IR)
<b>S/N ratio</b>	56dB
<b>White balance</b>	(AWB) Auto / manual

<b>WDR</b>	120dB
<b>Backlight compensation</b>	BLC / HLC / WDR(120dB)
<b>Shutter</b>	Auto / manual 1~1/100000s
<b>Gain control</b>	(AGC) Auto / manual
<b>Noise reduction</b>	2D/3D DNR
<b>Image rotate</b>	Mirror, Flip 0°/90°/180°/270°
<b>Stream support</b>	3
<b>Resolutions</b>	8M(3840×2160) / 5M(3072×1728) / 4M(2560×1440) / 2M(1920×1080) / 720P(1280×720) / D1(720×576) / (640×360) / 2CIF(704×288) / CIF(352×288)
<b>Main stream</b>	3840×2160@20fps 3072×1728@30fps 2560×1440@30fps 1920×1080@30fps 1280×720@30fps
<b>Second stream</b>	1920×1080@30fps 1280×720@30fps 720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
<b>Third stream</b>	720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
<b>Bitrate</b>	128Kbps~6144kbps
<b>Video compression</b>	H.265 / H.265+ / H.264 / H.264+ / MJPEG
<b>Day/night</b>	ICR
<b>Illuminator type</b>	IR LED
<b>Illuminator</b>	40m
<b>Microphone</b>	Yes
<b>Audio compression</b>	G.711
<b>Memory card slot</b>	microSD 256GB
<b>Support</b>	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
<b>Motion detect</b>	4
<b>Privacy masking</b>	4
<b>Network</b>	RJ-45 10/100Mbps
<b>Compatibility</b>	ONVIF(S/G/T)
<b>Protocols</b>	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
<b>Power supply type</b>	12VDC / PoE(802.3af)
<b>Power consumption</b>	max 9W
<b>Housing color</b>	Graphite
<b>IP class</b>	IP67
<b>IK10</b>	Yes
<b>Working environment</b>	-30°C~+60°C max 95% RH
<b>Dimensions</b>	Ø129×110mm
<b>Weight</b>	0.69kg
<b>Ai - Built-in intelligent functions</b>	Built-in intelligent algorithm of image analysis
<b>Ai - Perimeter protection</b>	Crossline, intrusion
<b>Ai - Human/vehicle detection</b>	Human/vehicle classification for crossline and intrusion reduces false alarms
<b>Ai - Face detection</b>	Face detection and tracking, snapshot
<b>Ai - People counting</b>	People counting for intrusion and crossline, counting people in/out

## Accessories



BCS-P-A172M-G



BCS-P-U112-G