

BCS-L-PSIP24425SCR10L5-Ai1



Index: 12841
GTIN13/EAN13: 5904890715554
URL: <https://bcs.pl/gb/4mpx/4466-bcs-l-psip24425scr10l5-ai1-5904890715554.html>



Product Details

Product	BCS-L-PSIP24425SCR10L5-Ai1
Brand	BCS LINE
Camera type	PTZ+stała
Resolution	4 Mpx
Resolution overview camera	4 Mpx
Sensor	1/2.8" CMOS STARVIS
Sensor overview camera	1/2.8" CMOS
Scanning system	Progressive Scan
Pixels	2560(H)×1440(V)
Pixels overview camera	2560(H)×1440(V)
RAM	1GB
RAM overview camera	1GB
ROM	4GB
ROM overview camera	4GB
Lens	motozoom
Focal length	5~125 mm
Focal lenght overview camera	2.8 mm
Aperture	F1.6~3.6
Aperture overview camera	F1.0

Focus	Auto / manual
Iris	Auto / manual
Optical zoom	25×
Digital zoom	16×
Angle of view	H: 51.9°~3.0° V: 39.7°~2.2° D: 63.1°~3.7°
Angle of view overview camera	H: 101° V: 53° D: 120°
DORI	Detect 100~2500m / Observe 40~1000m / Recognize 20~500m / Identify 10~250m
DORI overview camera	Detect 56m / Observe 22m / Recognize 11m / Identify 6m
Min illumination	0.005Lux(Color,F1.6,30IRE) 0.0005Lux(F1.6,B/W,30IRE) 0Lux(B/W,IR)
Min illumination overview camera	0.001Lux(Color,F1.0,30IRE) 0.0005Lux(F1.0,B/W,30IRE) 0Lux(B/W,IR)
S/N ratio	55dB
White balance	(AWB) Auto / manual
WDR	120dB
WDR overview camera	DWDR
Backlight compensation	BLC / HLC
Shutter	Auto / manual 1~1/30000s
Shutter overview camera	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	2D/3D DNR
RoI	Region of Interest
Image Stabilization	Electronic (EIS)
Defog	Electronic
Image rotate	Flip 180°
Stream support	3
Resolutions	4M(2560×1440) / 3M(2048×1536)(2304×1296) / 2M(1920×1080) / 1.3M(1280×960) / 720P(1280×720) / D1(704×576)(704×480) / VGA(640×480) / CIF(352×288)(352×240)
Resolutions overview camera	4M(2560×1440) / 3M(2048×1536)(2304×1296) / 2M(1920×1080) / 1.3M(1280×960) / 720P(1280×720) / D1(704×576)(704×480) / VGA(640×480) / CIF(352×288)(352×240)
Main stream	2560×1440 / 2304×1296 / 2048×1536 / 1920×1080 / 1280×960 / 1280×720(25/30fps)
Main stream overview camera	2560×1440 / 2304×1296 / 2048×1536 / 1920×1080 / 1280×960 / 1280×720(25/30fps)
Second stream	704×576 / 704×480 / 640×480 / 352×288 / 352×240(25/30fps)
Second stream overview camera	704×576 / 704×480 / 640×480 / 352×288 / 352×240(25/30fps)
Third stream	1920×1080 / 1280×960 / 1280×720(25/30fps)
Third stream overview camera	1920×1080 / 1280×960 / 1280×720(25/30fps)
Bitrate	H.264: 96 kbps~16384 kbps H.265: 38 kbps~10240 kbps
Bitrate overview camera	H.264: 96 kbps~16384 kbps H.265: 38 kbps~10240 kbps
Video compression	H.265 / H.265+ / H.264+ / H.264 / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED + WhiteLight
Illuminator type overview camera	IR LED + WhiteLight
IR range	100m
IR range overview camera	30m
WhiteLight range	50m
WhiteLight range overview camera	30m
NightColor	Yes
Loudspeaker	Yes
Active deterrence function ADC	Sound-optical alarm
Audio in	1
Audio out	1
Audio compression	G.711A / G.711Mu / G.726 / G.722.1 / G.723 / G.729 / MPEG2-L2 / PCM

Alarm in	2
Alarm out	1
Storage	FTP, SFTP, NAS
Memory card slot	microSD 512GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	Yes
Privacy masking	24
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	FTP, RTMP, IPv6, Bonjour, IPv4, DNS, RTCP, PPPoE, NTP, RTP, 802.1x, HTTPS, SNMP, TCP/IP, DDNS, UPnP, NFS, ICMP, UDP, IGMP, HTTP, SSL, DHCP, SMTP, Qos, RTSP, ARP
Power supply type	12VDC / PoE(802.3at)
Power consumption	max 25W
Housing color	White
IP class	IP66
Built-in heater	Yes
Surge protection	TVS 6kV
Working environment	-40°C~+65°C max 95% RH
Dimensions	160×184×304mm
Weight	3.41 kg
PAN speed	0.1°/s~200°/s(240°/s preset)
TILT speed	0.1°/s~120°/s(200°/s preset)
PAN range	0°~360°
TILT range	-15°~90° auto-flip, kamera stała 13°~23°
Auto tracking	Yes
Automatic functions	300 presets, 8 tour(32 presety), 5 pattern, 5 auto scan
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Intrusion, crossline, fast moving, loitering, people gathering, parking detection
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion and fast moving reduces false alarms
Ai - SMD - Smart Motion Detection	SMD 4.0
Accessories included	Wall mount

Accessories



BCS-AR



BCS-AS



BCS-ASD



BCS-ASDD



BCS-L-AR



BCS-L-AS