

BCS-P-DIP15FSR3-Ai



Index: 12902
GTIN13/EAN13: 5904890716087
URL: <https://bcs.pl/gb/5mpx/4447-bcs-p-dip15fsr3-ai-5904890716087.html>



Product Details

Product	BCS-P-DIP15FSR3-Ai
Brand	BCS POINT
NDAA	National Defense Authorization Act
Camera type	Dome
Resolution	5 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	2880(H)×1620(V)
Lens	fixed
Focal length	2.8 mm
Aperture	F1.6
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H: 110° V: 58.7° D: 130°
DORI	Detect 63m / Observe 25m / Recognize 13m / Identify 6m
Min illumination	0.003Lux(F1.6,AGC) 0Lux(B/W,IR)
S/N ratio	52dB
White balance	(AWB) Auto / manual

WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	2D/3D DNR
RoI	Region of Interest
Defog	Digital
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	2
Resolutions	5M(2880×1620) / 4M(2560×1440) / 3M(2304×1296) / 2M(1920×1080) / 720P(1280×720) / D1(720×576) / (640×360) / 2CIF(704×288) / CIF(352×288)
Main stream	2880×1620@25fps 2560×1440@25fps 2304×1296@30fps 1920×1080@30fps
Second stream	1280×720@30fps 720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
Bitrate	128Kbps~6144kbps
Video compression	H.265 / H.265+ / H.264 / MJPEG
Day/night	ICR
Illuminator type	IR LED
IR range	30m
Microphone	Yes
Audio compression	G.711A / G.711U
Storage	NAS(NFS)
Memory card slot	microSD 512GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS, 802.1x, SNMP
Network security	Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication RTSP, Digest Authentication HTTP, TLS 1.2, WSSE, Digest Authentication ONVIF, IP adress filtering
Power supply type	12VDC / PoE(802.3af)
Power consumption	max 4.4W
Housing color	White
IP class	IP67
IK10	Yes
Surge protection	4kV
Working environment	-30°C~+60°C max 95% RH
Dimensions	Ø109×81mm
Weight	0.36kg
Casing	Metal
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Rozpoznawanie człowieka dla wtargnięcia w obszar, przekroczenia linii redukuje fałszywe wywołanie alarmu.

Accessories



BCS-P-A173



BCS-P-U112



BCS-P-U113