

BCS-P-EIP25FSR3L3-Ai2(2)

Index: **12632** GTIN13/EAN13: 5904890714465

URL: <https://bcs.pl/gb/5mpx/4306-bcs-p-eip25fsr3l3-ai2-5904890714465.html>



BCS-P-EIP25FSR3L3-Ai2(2)

Product Details

Product	BCS-P-EIP25FSR3L3-Ai2(2)
Brand	BCS POINT
NDAA	National Defense Authorization Act
Camera type	Dome
Resolution	5 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	2880(H)×1620(V)
Lens	fixed
Focal length	2.8 mm
Aperture	F1.0
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H: 112.8° V: 59.4° D: 116.3°
DORI	Detect 63m / Observe 25m / Recognize 13m / Identify 6m
Min illumination	0.001Lux(F1.0,AGC) 0Lux(B/W,IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	130dB
Backlight compensation	BLC / HLC / WDR(130dB)
Shutter	Auto / manual 1~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	2D/3D DNR
RoI	Region of Interest
Defog	Digital
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	3
Resolutions	5M(2880×1620) / 4M(2560×1440) / 3M(2304×1296) / 2M(1920×1080) / 720P(1280×720) / D1(720×576) / (640×360) / 2CIF(704×288) / CIF(352×288)
Main stream	2880×1620@30fps 2560×1440@30fps 2304×1296@30fps 1920×1080@30fps 1280×720@30fps
Second stream	1280×720@30fps 720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
Third stream	720×576@30fps 640×360@30fps 704×288@30fps 352×288@30fps
Bitrate	128Kbps~16Mbps
Video compression	H.265 / H.265+ / H.264 / MJPEG
Day/night	ICR
Illuminator type	IR LED + WhiteLight
IR range	30m
WhiteLight range	30m
NightColor	Yes
Microphone	Yes
Loudspeaker	Yes

Active deterrence function ADC	Sound-optical alarm
Audio in	1
Audio out	1
Audio compression	G.711A / G.711U
Alarm in	1
Alarm out	1
Storage	NAS(NFS)
Memory card slot	microSD 512GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, SSL/TLS, SSH
Network security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic/digest authentication RTSP, Digest authentication HTTP, TLS 1.2, WSSE/digest authentication ONVIF
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 10W
Housing color	White
IP class	IP67
Surge protection	4kV
Working environment	-30°C~ +60°C max 95% RH
Dimensions	Ø129×118mm
Weight	0.69kg
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - People counting	People counting for intrusion and crossline, counting people in/out

BCS-P-EIP25FSR3L3-Ai2(2)

Accessories

BCS-P-A172M



BCS-P-U112(2)



BCS-ADU-B



BCS-ADU170

