

MC800

Control unit for
swing gates motors

Nice

MC800

Control unit for 230 V swing gates motors



With Nice BlueBUS technology, compatible with the Opera system for automation management, programming and diagnostics, including remotely.

Compatible with the Opera system whose multifunction O-View display (mountable in the box) enables the system to be personalised, modifying the opening and closing positions, staggered closing of the leaves and decelerations, diversifying the parameters such as force, speed and obstacle sensitivity for each motor..

Universal power supply: 120/230 VAC 50/60Hz

Microprocessor logic: the MC800 control unit combines the advantages of the Opera system with the advanced functions of the Nice systems (gradual start and deceleration, automatic memorising of both limit switch positions and pedestrian pass door function).

Safe and reliable: thanks to obstacle detection with double technology throughout the travel and possibility of connecting latest generation resistive sensitive edges.

Intelligent: on start-up, indicator to confirm correct power supply and efficient operation of the control unit; automatic fault diagnostics and signalling via the flashing light and confirmation LEDs.

Installation couldn't be simpler: thanks to the system BlueBUS, enabling connection of the control unit and accessories by means of just two wires.

Radio receiver: designed to take SM plug-in receivers.

TECHNICAL SPECIFICATIONS

Code	Description	Pack/Pallet
MC800	Control unit for one or two 230V motors with Nice BlueBUS technology compatible for the Opera system	1

Code	MC800
Power supply (Vac 50/60 Hz)	120/230
Max. motor power and current (W; A)	900; 15
Maximum accessories power 24 V (A)	0.2
Maximum flashing light power (V; W)	120/230; 21
Maximum gate open indicator power CA (V; W)	24; 4
Maximum electric lock power (Vac; VA)	12; 15
Working time "TL" (s)	-
Pause time "TP" (s)	5 - 180
Delay 1st motor in opening TRA (s)	Programmable
Delay 2nd motor in closing TRC (s)	Programmable
Courtesy light time TCOR (s)	0: 250
Pre-flashing time TPRE (s)	0: 10
Force adjustment (%)	-
Anti-crushing device (sensitivity)	min ÷ max
Case dimensions (mm)	230x120x300 h

COMMON ACCESSORIES



IBT4N

Interface for connecting the O-View programming unit.

Pc./Pack 1



MCA5

Spare control unit for MC800.

Pc./Pack 1



IT4WIFI


Smart Wi-fi interface to manage gates and garage doors by smartphone (*).

Pc./Pack 1

COMPATIBILITY GUIDE - MC800

Motor	Spare code	Receiver	Transmitter	Photocells	Flashing light
T04005, T04006, T04015, T04605, T05015, T05016, T05605, HY7100, HY7005, WG4000, WG5000, MFAB3000, MFAB3000L, LFAB4000, T003000, T004500	MCA5	OXI	ERA INTI, ERA ONE, ERA FLOR, NICEWAY, FLOR-S, FLOR-M, FLO, ONE, SMILO, VERY VR, VERY VE	EPSB, EPMB, EPLB, F210B, EPMOW, MOFB	ELAC, EL, ML, MLT, LUCY

Technology as simple as a gesture



Nice, easy solutions for Home and Building.

Systems for the automation and control of gates, garage doors, Blinds, shutters and alarm systems, with integrated management using smart and intuitive interfaces: practical, functional and elegant solutions to help you enjoy your living spaces to the full.

Nice

Nice SpA
Oderzo TV Italy

www.niceforyou.com



NiceLoveEarth

Nice cares for the environment.
Using natural paper it avoids excessive
use of raw materials and forest exploitation.
Waste is reduced, energy is saved and
climate quality is improved.

Our products and technologies are protected
with patents and design/ trademark
registrations. Any violation of our rights
will be legally prosecuted.